

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES

\* **NEVER** exceed the sidewall markings for the maximum loads and inflation pressures.  
 Note: Letters in parentheses denote Load Range for which Bold Face loads are maximum. International Load Index numbers are shown after the Load Range.

| Tire Size       | PSI    | 70      | 75   | 80      | 85      | 90      | 95      | 100     | 105     | 110     | 115     | 120     | 125     | 130      |
|-----------------|--------|---------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|----------|
| 215/75R17.5     | Dual   | 2570    | 2715 | 2860    | 3000    | 3140    | 3280    | 3420(F) | -       | -       | -       | -       | -       | -        |
|                 | Single | 2650    | 2800 | 2950    | 3095    | 3240    | 3385    | 3530(F) | -       | -       | -       | -       | -       | -        |
| 215/75R17.5     | Dual   | 2560    | 2695 | 2835    | 2980    | 3120    | 3255    | 3390    | 3530(G) | -       | -       | -       | -       | -        |
|                 | Single | 2710    | 2865 | 3015    | 3165    | 3310    | 3460    | 3605    | 3750(G) | -       | -       | -       | -       | -        |
| 225/70R19.5     | Dual   | 2720    | 2860 | 3000(E) | 3115    | 3245    | 3415(F) | 3490    | 3615    | 3750(G) | -       | -       | -       | -        |
|                 | Single | 2895    | 3040 | 3195(E) | 3315    | 3450    | 3640(F) | 3715    | 3845    | 3970(G) | -       | -       | -       | -        |
| 245/70R19.5     | Dual   | -       | -    | 3415    | 3515    | 3655    | 3860(F) | 3940    | 4075    | 4300(G) | 4345    | 4540(H) | -       | -        |
|                 | Single | -       | -    | 3640    | 3740    | 3890    | 4080(F) | 4190    | 4335    | 4540(G) | 4620    | 4805(H) | -       | -        |
| 265/70R19.5     | Dual   | -       | -    | 3750    | 3930    | 4095    | 4300    | 4405    | 4415    | 4675(G) | -       | -       | -       | -        |
|                 | Single | -       | -    | 3970    | 4180    | 4355    | 4540    | 4685    | 4850    | 5070(G) | -       | -       | -       | -        |
| 265/70R19.5     | Dual   | -       | -    | -       | 4235    | 4435    | 4630    | 4825    | 5015    | 5205(G) | -       | -       | -       | -        |
|                 | Single | -       | -    | -       | 4485    | 4695    | 4900    | 5105    | 5310    | 5510(G) | -       | -       | -       | -        |
| 285/70R19.5     | Dual   | -       | -    | 4200    | 4410    | 4615    | 4820    | 5020    | 5220    | 5420    | 5615    | 5810    | 6005(H) | -        |
|                 | Single | -       | -    | 4470    | 4695    | 4915    | 5130    | 5345    | 5560    | 5770    | 5980    | 6185    | 6395(H) | -        |
| 8R19.5          | Dual   | 2460    | 2570 | 2680(D) | 2785    | 2890    | 3000(E) | 3100    | 3200    | 3305(F) | -       | -       | -       | -        |
|                 | Single | 2540    | 2680 | 2835(D) | 2955    | 3075    | 3195(E) | 3305    | 3415    | 3525(F) | -       | -       | -       | -        |
| 8.25R20         | Dual   | 3270    | 3410 | 3550    | 3690    | 3840(E) | 4005    | 4150    | 4300(F) | 4425    | 4550    | 4675(G) | -       | -        |
|                 | Single | 3370    | 3560 | 3730    | 3890    | 4080(E) | 4235    | 4390    | 4540(F) | 4675    | 4810    | 4940(G) | -       | -        |
| 9.00R20         | Dual   | 3860(D) | 4045 | 4230    | 4410(E) | 4585    | 4760    | 4940(F) | 5080    | 5220    | 5355(G) | -       | -       | -        |
|                 | Single | 4080(D) | 4280 | 4480    | 4675(E) | 4850    | 5025    | 5205(F) | 5360    | 5515    | 5675(G) | -       | -       | -        |
| 10.00R20        | Dual   | 4380    | 4580 | 4760    | 4950    | 5205(F) | 5415    | 5625    | 5840(G) | 5895    | 5950    | 6005(H) | -       | -        |
|                 | Single | 4530    | 4770 | 4990    | 5220    | 5510(F) | 5730    | 5950    | 6175(G) | 6320    | 6465    | 6610(H) | -       | -        |
| 11.00R20        | Dual   | 4780    | 4990 | 5190    | 5390    | 5675(F) | 5785    | 5895    | 6005(G) | 6265    | 6525    | 6780(H) | -       | -        |
|                 | Single | 4940    | 5200 | 5450    | 5690    | 6005(F) | 6205    | 6405    | 6610(G) | 6870    | 7130    | 7390(H) | -       | -        |
| 12.00R20        | Dual   | 5440    | 5680 | 5910    | 6140    | 6360    | 6610(G) | 6790    | 6970    | 7160(H) | 7390    | 7610(J) | -       | -        |
|                 | Single | 5620    | 5920 | 6200    | 6480    | 6740    | 7160(G) | 7380    | 7600    | 7830(H) | 8050    | 8270(L) | -       | -        |
| 11.00R22        | Dual   | 5080    | 5300 | 5520    | 5730    | 5840(F) | 6095    | 6350    | 6610(G) | 6790    | 6970    | 7160(H) | -       | -        |
|                 | Single | 5240    | 5520 | 5790    | 6040    | 6395(F) | 6650    | 6910    | 7160(G) | 7380    | 7600    | 7830(H) | -       | -        |
| 245/75R22.5*    | Dual   | 3160    | 3315 | 3525    | 3615    | 3765    | 3970    | 4055    | 4195    | 4300(G) | -       | -       | -       | -        |
|                 | Single | 3470    | 3645 | 3860    | 3975    | 4140    | 4300    | 4455    | 4610    | 4675(G) | -       | -       | -       | -        |
| 255/70R22.5     | Dual   | -       | -    | 3970    | 4110    | 4275    | 4410    | 4455    | 4610    | 4675(G) | 4915    | 5070(H) | -       | -        |
|                 | Single | -       | -    | 4190    | 4370    | 4550    | 4675    | 4895    | 5065    | 5205(G) | 5400    | 5510(H) | -       | -        |
| 265/75R22.5**   | Dual   | 3525    | 3705 | 3860    | 4040    | 4205    | 4410    | 4525    | 4685    | 4805(G) | -       | -       | -       | -        |
|                 | Single | 3875    | 4070 | 4300    | 4440    | 4620    | 4805    | 4975    | 5150    | 5205(G) | -       | -       | -       | -        |
| 275/70R22.5     | Dual   | 3895    | 4115 | 4335    | 4550    | 4765    | 4975    | 5180    | 5390    | 5590    | 5795    | 5995    | 6195    | 6395(H)  |
|                 | Single | 4230    | 4470 | 4705    | 4940    | 5175    | 5400    | 5630    | 5850    | 6075    | 6295    | 6510    | 6730    | 6945(H)  |
| 295/75R22.5***  | Dual   | 4095    | 4300 | 4540    | 4690    | 4885    | 5070(F) | 5260    | 5440    | 5675(G) | 5795    | 6005(H) | -       | -        |
|                 | Single | 4500    | 4725 | 4940    | 5155    | 5370    | 5510(F) | 5780    | 5980    | 6175(G) | 6370    | 6610(H) | -       | -        |
| 295/75R22.5**** | Dual   | -       | -    | -       | -       | -       | 5305    | 5530    | 5750    | 5965    | 6185    | 6400    | 6610(H) | -        |
|                 | Single | -       | -    | -       | -       | -       | 5750    | 5990    | 6230    | 6465    | 6700    | 6930    | 7160(H) | -        |
| 295/80R22.5     | Dual   | 4360    | 4610 | 4855    | 5095    | 5335    | 5570    | 5805    | 6035    | 6265    | 6490    | 6715    | 6940(H) | -        |
|                 | Single | 4920    | 5200 | 5475    | 5750    | 6020    | 6285    | 6545    | 6810    | 7045    | 7320    | 7575    | 7830(H) | -        |
| 305/70R22.5     | Dual   | 4405    | 4655 | 4900    | 5145    | 5385    | 5625    | 5860    | 6095    | 6325    | 6555    | 6780(J) | -       | -        |
|                 | Single | 4800    | 5075 | 5345    | 5610    | 5870    | 6130    | 6385    | 6640    | 6895    | 7145    | 7390(J) | -       | -        |
| 305/70R22.5     | Dual   | -       | -    | -       | -       | 5505    | 5750    | 5990    | 6230    | 6465    | 6700    | 6930    | 7160    | 7390(L)  |
|                 | Single | -       | -    | -       | -       | 5835    | 6090    | 6350    | 6600    | 6850    | 7100    | 7345    | 7590    | 7830(L)  |
| 315/80R22.5     | Dual   | -       | -    | 5675    | 5840    | 6070    | 6395    | 6545    | 6770    | 6940    | 7210    | 7610    | 8010    | 8270(L)  |
|                 | Single | -       | -    | 6175    | 6415    | 6670    | 6940    | 7190    | 7440    | 7610    | 7920    | 8270    | 8810    | 9090(L)  |
| 315/80R22.5     | Dual   | -       | -    | -       | -       | 5505    | 5750    | 5990    | 6230    | 6465    | 6700    | 6930    | 7160    | 7390(L)  |
|                 | Single | -       | -    | -       | -       | 6980    | 7290    | 7595    | 7900    | 8200    | 8495    | 8790    | 9080    | 9370(L)  |
| 315/80R22.5**** | Dual   | 5030    | 5315 | 5595    | 5875    | 6150    | 6420    | 6690    | 6955    | 7220    | 7480    | 7740    | 8000    | 8255(L)  |
|                 | Single | 6090    | 6440 | 6780    | 7115    | 7450    | 7780    | 8105    | 8425    | 8745    | 9065    | 9375    | 9690    | 10000(L) |
| 9R22.5          | Dual   | 3270    | 3410 | 3550    | 3690    | 3840(E) | 4005    | 4150    | 4300(F) | 4425    | 4550    | 4675(G) | -       | -        |
|                 | Single | 3370    | 3560 | 3730    | 3890    | 4080(E) | 4235    | 4390    | 4540(F) | 4675    | 4810    | 4940(G) | -       | -        |
| 10R22.5         | Dual   | 3860    | 4045 | 4230    | 4410(E) | 4585    | 4760    | 4940(F) | 5075    | 5210    | 5355(G) | -       | -       | -        |
|                 | Single | 4080    | 4280 | 4480    | 4675(E) | 4850    | 5025    | 5205(F) | 5360    | 5515    | 5675(G) | -       | -       | -        |
| 11R22.5         | Dual   | 4380    | 4580 | 4760    | 4950    | 5205(F) | 5415    | 5625    | 5840(G) | 5895    | 5950    | 6005(H) | -       | -        |
|                 | Single | 4530    | 4770 | 4990    | 5220    | 5510(F) | 5730    | 5950    | 6175(G) | 6320    | 6465    | 6610(H) | -       | -        |
| 11R22.5         | Dual   | -       | -    | -       | -       | 5205    | 5415    | 5625    | 5840    | 5895    | 5950    | 6005(H) | -       | -        |
|                 | Single | -       | -    | -       | -       | 5510    | 5730    | 5950    | 6175    | 6320    | 6465    | 6610(H) | -       | -        |
| 12R22.5*****    | Dual   | 4780    | 4990 | 5190    | 5390    | 5675(F) | 5785    | 5895    | 6005(G) | 6265    | 6525    | 6780(H) | -       | -        |
|                 | Single | 4940    | 5200 | 5450    | 5690    | 6005(F) | 6205    | 6405    | 6610(G) | 6870    | 7130    | 7390(H) | -       | -        |
| 285/75R24.5     | Dual   | 4135    | 4340 | 4540    | 4740    | 4930    | 5205(F) | 5310    | 5495    | 5675(G) | 5860    | 6175(H) | -       | -        |
|                 | Single | 4545    | 4770 | 4940    | 5210    | 5420    | 5675(F) | 5835    | 6040    | 6175(G) | 6440    | 6780(H) | -       | -        |
| 11R24.5         | Dual   | 4660    | 4870 | 5070    | 5260    | 5510(F) | 5675    | 5840    | 6005(G) | 6205    | 6405    | 6610(H) | -       | -        |
|                 | Single | 4820    | 5070 | 5310    | 5550    | 5840(F) | 6095    | 6350    | 6610(G) | 6790    | 6970    | 7160(H) | -       | -        |

\* Equivalent to Michelin 235/80R22.5  
 \*\* Equivalent to Michelin 255/80R22.5  
 \*\*\* Equivalent to Michelin 275/80R22.5  
 \*\*\*\* For M320Z only.  
 \*\*\*\*\* Equivalent to Michelin 295/80R22.5

NOTE: All data shown here is approximately what you would find under normal conditions and is subject to change without notice. Though every effort has been taken to ensure the accuracy of this data shown here, legal responsibility cannot be accepted by Toyo Tire U.S.A. or Toyo Tire & Rubber Co., Ltd., for any damage or loss coming from any undetected errors or any misprint.

TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES

\* **NEVER** exceed the sidewall markings for the maximum loads and inflation pressures.  
 Note: Letters in parentheses denote Load Range for which Bold Face loads are maximum. International Load Index numbers are shown after the Load Range.

| Tire Size    | PSI    | 70   | 75   | 80   | 85         | 90         | 95         | 100        | 105        | 110        | 115        | 120        | 125 | 130 |
|--------------|--------|------|------|------|------------|------------|------------|------------|------------|------------|------------|------------|-----|-----|
| 10R22.5      | Dual   | 3860 | 4045 | 4230 | 4410(E)132 | 4585       | 4760       | 4940(F)136 | 5075       | 5210       | 5355(G)139 | -          | -   | -   |
|              | Single | 4080 | 4280 | 4480 | 4675(E)134 | 4850       | 5025       | 5205(F)138 | 5360       | 5515       | 5675(G)141 | -          | -   | -   |
| 11R22.5      | Dual   | 4380 | 4580 | 4760 | 4950       | 5205(F)138 | 5415       | 5625       | 5840(G)142 | 5895       | 5950       | 6005(H)143 | -   | -   |
|              | Single | 4530 | 4770 | 4990 | 5220       | 5510(F)140 | 5730       | 5950       | 6175(G)144 | 6320       | 6465       | 6610(H)146 | -   | -   |
| 12R22.5***** | Dual   | 4780 | 4990 | 5190 | 5390       | 5675(F)141 | 5785       | 5895       | 6005(G)143 | 6265       | 6525       | 6780(H)147 | -   | -   |
|              | Single | 4940 | 5200 | 5450 | 5690       | 6005(F)143 | 6205       | 6405       | 6610(G)146 | 6870       | 7130       | 7390(H)150 | -   | -   |
| 285/75R24.5  | Dual   | 4185 | 4340 | 4540 | 4740       | 4930       | 5205(F)138 | 5310       | 5495       | 5675(G)141 | -          | -          | -   | -   |
|              | Single | 4545 | 4770 | 4940 | 5210       | 5420       | 5675(F)141 | 5835       | 6040       | 6175(G)144 | -          | -          | -   | -   |
| 11R24.5      | Dual   | 4660 | 4870 | 5070 | 5260       | 5510(F)140 | 5675       | 5840       | 6005(G)143 | 6205       | 6405       | 6610(H)146 | -   | -   |
|              | Single | 4820 | 5070 | 5310 | 5550       | 5840(F)142 | 6095       | 6350       | 6610(G)146 | 6790       | 6970       | 7160(H)149 | -   | -   |

| Tire Size   | PSI    | 70   | 75   | 80   | 85   | 90   | 95   | 100  | 105  | 110  | 115  | 120     | 125 | 130 |
|-------------|--------|------|------|------|------|------|------|------|------|------|------|---------|-----|-----|
| 14/80R20    | Single | 5870 | 6205 | 6535 | 6860 | 7180 | 7495 | 7810 | 8120 | 8430 | 8735 | 9040(J) | -   | -   |
| 385/65R22.5 | Single | 6380 | 6720 | 6940 | 7350 | 7650 |      |      |      |      |      |         |     |     |