

TOYO TIRES®

TOYO TIRES®



TOYOTIRES.COM

TOYO TIRE U.S.A. CORP.
P.O. BOX 6052
CYPRESS, CA 90630
800.442.8696

WINTER

ENGINEERED FOR THE ELEMENTS



©2014 Toyo Tire U.S.A. Corp.
Published August 2014

#0180242



WE ARE STURDY AND STRONG AND LIVE FOR FRESH TRACKS.



Bring on the winter because these specialty tires are engineered to excel in snow and ice. Our advanced technologies provide drivers with improved traction and a comfortable ride in harsh conditions. And whether you choose a studless or studdable tire, Mother Nature won't keep you from where you want to go.

From the durability and excellent performance of the GSi-5 to the exceptional handling and traction of our winter performance tire, the Observe Garit KX, winter weather will never get in your way.

For areas with more severe winter weather, the studdable Observe G3-Ice gives you outstanding snow and ice traction with driving comfort. If you're driving a light truck or SUV, the Open Country WLT1 delivers confident ice and snow performance with the tread life you need for the long haul.

TOYO TIRES. DRIVEN TO PERFORM.

INNOVATION

Toyo Tires' line of studless and studdable winter tires is built with features that provide proven traction in snow and on ice without sacrificing a comfortable ride.

WALNUTS MAKE THE DIFFERENCE



Microbit technology is an exclusive Toyo® production technique that embeds thousands of ground walnut shells within the tread. These unique bits dig and bite into the ice and snow for improved traction, offering a more comfortable, eco-friendly alternative to studded winter tires.

SIPES IMPROVE TRACTION AND HANDLING



Thousands of high-density sipes provide more biting edges for increased snow traction.

BUILT FOR SEVERE SNOW CONDITIONS



Tires meeting a higher level of snow traction set forth by the U.S. Rubber Manufacturers Association (RMA) and the Rubber Association of Canada (RAC) receive a mountain/snowflake symbol branded on the tire's sidewall. Tires that meet these standards feature unique tread patterns, construction elements, and other materials that provide superior snow performance. All Toyo winter tires brandish the mountain/snowflake symbol.



OBSERVE® GSI-5
STUDLESS PASSENGER /CUV/SUV
WINTER TIRE



OBSERVE® GARIT® KX
STUDLESS PERFORMANCE WINTER TIRE



OBSERVE® G3-ICE
STUDDABLE PASSENGER/LIGHT TRUCK
WINTER TIRE



OPEN COUNTRY® WLT1
STUDLESS LIGHT TRUCK WINTER TIRE

OBSERVE® GSI-5

STUDLESS PASSENGER/CUV/SUV WINTER TIRE

The Observe GSi-5 provides excellent performance for demanding winter road conditions. Improved ice and snow capabilities, as well as long wear life, are the benefits of advanced design, technology, and compounding.

- Advanced tread compound enhances wet grip, braking, and traction in low temperatures.
- Absorbent carbonic powder offers better contact and increased safety as carbonic powder created from bamboo absorbs moisture on the road.
- Microbit technology improves traction as ground walnut shells dig and bite into snow and ice.



Mountain Snowflake qualified for severe snow conditions.

OBSERVE® GARIT® KX

STUDLESS PERFORMANCE WINTER TIRE

When the conditions turn to snow and ice, the Observe Garit KX is the tire for your sports car. This unidirectional winter performance tire has an H-speed rating and is designed for traction in harsh winter conditions.

- Advanced tread compound enhances wet grip, braking, and traction in low temperatures.
- Microbit technology improves traction as ground walnut shells dig and bite into the snow and ice.
- Saw-toothed blocks improve traction as they cut through the thin water layer on ice.



Mountain Snowflake qualified for severe snow conditions.

OBSERVE® G3-ICE

STUDDABLE PASSENGER/LIGHT TRUCK WINTER TIRE

Designed for tough winter conditions, the Observe G3-Ice combines excellent performance with driving comfort. For areas that experience severe winters, this tire can be studded for added traction on ice and compacted snow. Optimized stud hole placement delivers better traction and a quieter ride with fewer studs.

- New softer, high-silica compound ensures tread blocks remain flexible and enhances wet braking and handling even in lower temperatures.
- Optimized stud hole placement improves road contact and traction with fewer studs, reducing noise, resulting in a quieter ride.
- Large U-shaped tread blocks with saw-tooth edges grab onto the snow for better traction and braking.

OPEN COUNTRY® WLT1

STUDLESS LIGHT TRUCK WINTER TIRE

Tough winter jobs just got a little bit easier. The Open Country WLT1 provides excellent winter driving capabilities for a variety of heavy-duty light trucks, including pickups, vans, and SUVs. Designed to handle the increased load-carrying capacity of these vehicles, it delivers confident ice and snow performance with long tread life.

- Wider tread footprint improves stability and handling.
- Wider deep grooves increase snow traction and prevent snow buildup.
- Increased sipe density improves water evacuation, ice traction, and cornering performance on ice.



Mountain Snowflake qualified for severe snow conditions.

Observe G3-Ice shown with winter studs. Pinned to accept TSMI #11 stud.



Mountain Snowflake qualified for severe snow conditions.

toyotires.com

OBSERVE® GSI-5

SPECIFICATIONS

OBSERVE® GSI-5

SPECIFICATIONS

TIRE SIZE	LOAD/ SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX PRESSURE (PSI)	REVS PER MILE
						OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	MAX LOAD (LBS)		
145/65R15	72T	SL	BSW	4.0-(4.5)-5.0	11.0	22.5	5.9	783	44	923
175/55R15	77T	SL	BSW	5.0-(5.5)-6.0	11.3	22.6	7.1	908	44	921
175/65R15	84T	SL	BSW	(5.0)-6.0	12.0	24.0	7.1	1102	44	865
185/55R15	82T	SL	BSW	5.0-(6.0)-6.5	12.0	23.0	7.6	1047	44	901
185/60R15	84T	SL	BSW	5.0-(5.5)-6.5	12.0	23.8	7.4	1102	44	874
185/65R15	88T	SL	BSW	5.0-(5.5)-6.5	12.0	24.5	7.6	1235	44	848
195/60R15	88T	SL	BSW	5.5-(6.0)-7.0	12.0	24.3	7.9	1235	44	854
195/65R15	91T	SL	BSW	5.5-(6.0)-7.0	12.0	25.0	8.0	1356	44	833
205/60R15	91T	SL	BSW	5.5-(6.0)-7.5	12.0	24.7	8.1	1356	44	841
205/65R15	94T	SL	BSW	5.5-(6.0)-7.5	12.0	25.5	8.0	1477	44	816
P205/70R15	95T	SL	BSW	5.0-(6.0)-7.0	12.0	26.3	8.2	1499	44	791
P205/75R15	97T	SL	BSW	5.0-(5.5)-7.0	12.0	27.1	7.9	1598	44	766
215/60R15	94T	SL	BSW	6.0-(6.5)-7.5	12.0	25.2	8.7	1477	44	825
215/65R15	96T	SL	BSW	6.0-(6.5)-7.5	12.0	26.0	8.7	1565	44	798
215/70R15	98T	SL	BSW	5.5-(6.5)-7.0	12.0	26.8	8.7	1653	44	775
P215/75R15	100T	SL	BSW	5.5-(6.0)-7.0	12.0	27.6	8.3	1742	44	752
225/70R15	100T	SL	BSW	6.0-(6.5)-7.5	12.7	27.4	9.0	1764	44	759
P225/75R15	102T	SL	BSW	(6.0)-7.5	13.4	28.2	8.8	1874	44	735
235/75R15	105T	SL	BSW	6.0-(6.5)-8.0	13.4	28.8	9.3	2039	44	722
265/75R15	112T	SL	BSW	7.0-(7.5)-9.0	14.0	30.6	10.6	2469	44	678
185/55R16	83H	SL	BSW	5.0-(6.0)-6.5	12.0	24.1	7.6	1074	51	862
195/50R16	84T	SL	BSW	5.5-(6.0)-7.0	12.0	23.8	7.8	1102	44	874
195/55R16	87T	SL	BSW	5.5-(6.0)-7.0	12.0	24.5	7.8	1201	44	848
205/55R16	94T	XL	BSW	5.5-(6.5)-7.5	12.0	24.9	8.4	1477	50	835
205/60R16	92T	SL	BSW	5.5-(6.0)-7.5	12.0	25.7	8.1	1389	44	809
205/65R16	95T	SL	BSW	5.5-(6.0)-7.5	12.0	26.5	8.2	1521	44	785
P205/70R16	96S	SL	BSW	5.0-(6.0)-7.0	12.0	27.3	8.1	1565	44	761
215/60R16	95T	SL	BSW	6.0-(6.5)-7.5	12.0	26.2	8.7	1521	44	793
215/65R16	98T	SL	BSW	6.0-(6.5)-7.5	12.0	27.0	8.7	1653	44	769
215/70R16	100S	SL	BSW	5.5-(6.5)-7.0	12.0	27.8	8.6	1764	44	746
215/75R16	103S	SL	BSW	5.5-(6.0)-7.0	13.4	28.7	8.2	1929	44	724
225/60R16	98T	SL	BSW	6.0-(6.5)-8.0	12.7	26.6	8.9	1653	44	781
225/65R16	100T	SL	BSW	6.0-(6.5)-8.0	12.0	27.5	9.0	1764	44	756
225/70R16	103S	SL	BSW	6.0-(6.5)-7.5	12.7	28.4	8.9	2094	44	731
225/75R16	104S	SL	BSW	(6.0)-7.5	13.4	29.2	8.8	1984	44	711
235/60R16	100S	SL	BSW	6.5-(7.0)-8.5	13.4	27.1	9.5	1764	44	767
235/65R16	103T	SL	BSW	6.5-(7.0)-8.5	13.4	28.0	9.5	1929	44	742
235/70R16	106S	SL	BSW	6.0-(7.0)-8.0	13.4	29.0	9.5	2094	44	716
235/75R16	108S	SL	BSW	6.0-(6.5)-8.0	13.4	29.8	9.3	2205	44	697
245/70R16	107S	SL	BSW	6.5-(7.0)-8.0	13.4	29.5	9.8	2149	44	704
245/75R16	111S	SL	BSW	6.5-(7.0)-8.0	13.4	30.5	9.8	2403	44	682
255/70R16	111S	SL	BSW	6.5-(7.5)-8.5	13.4	30.1	10.3	2403	44	691
265/70R16	112S	SL	BSW	7.0-(8.0)-9.0	14.0	30.6	10.8	2469	44	679
265/75R16	116S	SL	BSW	7.0-(7.5)-9.0	14.0	31.6	10.7	2756	44	657
205/50R17	93T	XL	BSW	5.5-(6.5)-7.5	12.0	25.1	8.3	1433	50	827
215/60R17	96T	SL	BSW	6.0-(6.5)-7.5	12.0	27.3	8.6	1565	44	761
P215/65R17	98T	SL	BSW	6.0-(6.5)-7.5	12.7	28.1	8.6	1653	44	740

TIRE SIZE	LOAD/ SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX PRESSURE (PSI)	REVS PER MILE
						OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	MAX LOAD (LBS)		
225/60R17	99T	SL	BSW	6.0-(6.5)-8.0	12.7	27.8	8.9	1709	44	747
225/65R17	102S	SL	BSW	6.0-(6.5)-8.0	12.7	28.5	8.8	1874	44	728
235/55R17	99H	SL	BSW	6.5-(7.5)-8.5	12.0	27.2	9.5	1709	51	765
235/60R17	102T	SL	BSW	6.5-(7.0)-8.5	13.4	28.1	9.4	1874	44	739
235/65R17	104S	SL	BSW	6.5-(7.0)-8.5	13.4	29.1	9.3	1984	44	714
245/65R17	107S	SL	BSW	(7.0)-8.5	13.4	29.5	9.7	2149	44	704
245/70R17	110S	SL	BSW	6.5-(7.0)-8.0	13.4	30.5	9.8	2337	44	680
255/60R17	106T	SL	BSW	7.0-(7.5)-9.0	13.4	29.1	10.3	2094	44	715
P255/70R17	110S	SL	BSW	6.5-(7.5)-8.5	13.4	31.1	10.2	2337	44	668
265/65R17	112S	SL	BSW	7.5-(8.0)-9.5	14.0	30.5	10.7	2469	44	681
265/70R17	115S	SL	BSW	7.0-(8.0)-9.0	14.0	31.6	10.8	2679	44	657
P285/70R17	117S	SL	BSW	7.5-(8.5)-9.5	14.0	32.7	11.5	2833	44	636
P215/55R18	94T	SL	BSW	6.0-(7.0)-7.5	12.0	27.3	8.8	1477	44	761
225/55R18	98T	SL	BSW	6.0-(7.0)-8.0	12.0	27.8	9.1	1653	44	748
225/60R18	100T	SL	BSW	6.0-(6.5)-8.0	12.7	28.7	8.9	1764	44	725
235/55R18	97H	SL	BSW	6.5-(7.5)-8.5	12.0	27.4	9.5	1609	51	759
235/55R18	100H	SL	BSW	6.5-(7.5)-8.5	12.0	28.2	9.5	1764	51	736
235/60R18	107S	XL	BSW	6.5-(7.0)-8.5	13.4	29.2	9.4	2149	50	712
235/65R18	106S	SL	BSW	6.5-(7.0)-8.5	13.4	30.0	9.4	2094	44	692
245/60R18	105T	SL	BSW	7.0-(7.0)-8.5	13.4	29.6	9.7	2039	44	703
245/55R18	109H	XL	BSW	7.0-(8.0)-9.0	12.5	29.0	10.2	2271	50	716
P255/65R18	109T	SL	BSW	7.0-(7.5)-9.0	13.4	31.0	10.2	2271	44	670
P255/70R18	112T	SL	BSW	6.5-(7.5)-8.5	13.4	32.0	10.4	2469	44	648
265/60R18	110S	SL	BSW	7.5-(8.0)-9.5	14.0	30.5	10.7	2337	44	682
265/65R18	114T	SL	BSW	7.5-(8.0)-9.5	14.0	31.5	10.8	2601	44	660
P265/70R18	114S	SL	BSW	7.0-(8.0)-9.0	14.0	32.6	10.7	2601	44	636
P275/65R18	114T	SL	BSW	7.5-(8.0)-9.5	14.0	32.0	11.1	2601	44	648
P225/55R19	99H	SL	BSW	6.0-(7.0)-8.0	12.0	28.8	9.1	1709	51	721
235/50R19	99H	SL	BSW	6.5-(7.5)-8.5	12.0	28.3	9.4	1709	51	733
235/55R19	101T	SL	BSW	6.5-(7.5)-8.5	12.0	29.2	9.5	1819	44	711
P245/55R19	103T	SL	BSW	7.0-(7.5)-8.5	12.0	29.7	9.8	1929	44	700
255/50R19	107H	XL	BSW	7.0-(8.0)-9.0	12.5	29.1	10.3	2149	50	713
255/55R19	111H	XL	BSW	7.0-(8.0)-9.0	12.5	30.1	10.3	2403	50	691
P255/60R19	108T	SL	BSW	7.0-(7.5)-9.0	13.4	31.0	10.3	2205	44	670
275/55R19	111T	SL	BSW	7.5-(8.5)-9.5	12.5	30.9	11.1	2403	44	671
285/45R19	111H	XL	BSW	9.0-(9.5)-10.5	12.5	29.0	11.2	2403	50	716
P235/55R20	102T	SL	BSW	6.5-(7.5)-8.5	12.0	30.3	9.6	1874	44	686
P245/50R20	102T	SL	BSW	7.0-(7.5)-8.5	12.0	29.8	9.7	1874	44	697
255/55R20	111H	XL	BSW	7.0-(8.0)-9.0	12.5	31.1	10.3	2403	50	669
P245/50R20	106H	SL	BSW	7.5-(8.5)-9.5	12.5	30.6	10.7	2094	51	680
275/40R20	106H	XL	BSW	9.0-(9.5)-11.0	12.5	28.8	10.7	2094	50	721
275/55R20	113T	SL	BSW	7.5-(8.5)-9.5	12.5	31.9	11.1	2535	44	651
P275/60R20	114T	SL	BSW	7.5-(8.0)-9.5	14.0	33.0	10.9	2601	44	630
315/35R20	110H	XL	BSW	10.5-(11.5)-12.5	12.5	28.8	12.2	2337	50	722

Speed rated "S" = 112mph, "T" = 118mph, "H" = 130mph. "SL" = Standard Load, "XL" = Extra Load. "BSW" = Black Sidewall. Bold designates measuring rim width. For the latest tire information, please visit toyotires.com.

OBSERVE® GARIT® KX

SPECIFICATIONS

OPEN COUNTRY® WLT1

SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
						OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	MAX LOAD (LBS)			
195/55R15	85H	SL	BSW	5.5- (6.0) -7.0	11.6	23.3	7.9	1135	51	890	
195/50R16	84H	SL	BSW	5.5- (6.0) -7.0	11.6	23.7	7.9	1102	51	878	
195/55R16	87H	SL	BSW	5.5- (6.0) -7.0	11.6	24.4	8.0	1201	51	852	
205/50R16	87H	SL	BSW	5.5- (6.5) -7.5	12.2	24.1	8.4	1201	51	862	
205/55R16	94H	XL	BSW	5.5- (6.5) -7.5	12.2	24.9	8.5	1477	50	835	
205/55R16	94Q	XL	BSW	5.5- (6.5) -7.5	12.2	25.0	8.4	1522	50	832	
215/55R16	97H	XL	BSW	6.0- (7.0) -7.5	12.2	25.3	8.9	1609	50	822	
225/50R16	92H	SL	BSW	6.0- (7.0) -8.0	12.2	25.0	9.1	1389	51	830	
225/55R16	99H	XL	BSW	6.0- (7.0) -8.0	12.2	25.8	9.3	1709	50	806	
205/50R17	93H	XL	BSW	5.5- (6.5) -7.5	12.2	25.2	8.3	1433	50	825	
215/45R17	91H	XL	BSW	(7.0) -8.0	12.2	24.7	8.5	1356	50	840	
215/50R17	95H	XL	BSW	6.0- (7.0) -7.5	11.6	25.5	8.6	1521	50	814	
215/55R17	94H	SL	BSW	6.0-(7.0)-7.5	12.2	26.4	9.0	1477	51	786	
225/45R17	94H	XL	BSW	7.0- (7.5) -8.5	12.2	25.0	9.1	1477	50	831	
225/50R17	94H	SL	BSW	6.0- (7.0) -8.0	12.2	25.9	8.9	1477	51	802	
225/55R17	97H	SL	BSW	6.0- (7.0) -8.0	12.2	26.8	9.2	1609	51	776	
235/45R17	97H	XL	BSW	7.5- (8.0) -9.0	12.2	25.4	9.5	1609	50	819	
235/50R17	96H	SL	BSW	6.5- (7.5) -8.5	12.2	26.3	9.5	1565	51	791	
245/45R17	99H	XL	BSW	7.5- (8.0) -9.0	12.2	25.7	9.7	1709	50	807	
225/45R18	91H	SL	BSW	7.0- (7.5) -8.5	12.2	26.1	8.9	1356	51	797	
225/50R18	95H	SL	BSW	6.0- (7.0) -8.0	12.2	26.9	9.0	1521	51	771	
235/45R18	98H	XL	BSW	7.5- (8.0) -9.0	12.2	26.5	9.4	1653	50	785	
245/45R18	96H	SL	BSW	7.5-(8.0)-9.0	12.2	26.8	9.6	1565	51	776	
245/40R19	94H	SL	BSW	8.0- (8.5) -9.5	12.2	26.7	9.7	1477	51	778	

TIRE SIZE	LOAD/SPEED	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)		MAX PRESSURE (PSI)	REVS PER MILE
					OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	SINGLE	DUAL			
LT215/85R16 E	115/112Q	BSW	5.5- (6.0) -7.0	15.9	30.4	8.9	2680	2470	80	683	
LT225/75R16 E	115/112Q	BSW	(6.0) -7.0	16.1	29.4	8.9	2680	2470	80	707	
LT235/85R16 E	120/116Q	BSW	6.0- (6.5) -7.5	16.1	31.9	9.3	3042	2778	80	652	
LT245/75R16 E	120/116Q	BSW	6.5- (7.0) -8.0	16.3	30.6	9.9	3042	2778	80	680	
LT265/75R16 E	123/120Q	BSW	7.0- (7.5) -8.0	16.5	31.7	10.7	3415	3085	80	655	
LT285/75R16 E	126/123Q	BSW	7.5- (8.0) -9.0	16.5	32.8	11.4	3750	3415	80	633	
LT225/75R17 E	116/113Q	BSW	(6.0) -7.5	16.1	30.4	8.9	2755	2535	80	683	
LT235/80R17 E	120/117Q	BSW	6.0- (6.5) -7.5	16.1	31.9	9.4	3085	2835	80	651	
LT245/70R17 E	119/116Q	BSW	6.5- (7.0) -8.0	16.3	30.6	9.7	3000	2755	80	678	
LT245/75R17 E	121/118Q	BSW	6.5- (7.0) -7.5	16.3	31.6	9.8	3195	2910	80	658	
LT265/70R17 E	121/118Q	BSW	7.0- (8.0) -8.5	16.5	31.8	10.7	3195	2910	80	654	
LT285/70R17 E	121/118Q	BSW	7.5- (8.5) -9.0	16.5	32.8	11.5	3195	2910	80	633	
LT275/65R18 E	123/120Q	BSW	7.5- (8.0) -9.0	16.5	32.3	10.9	3415	3085	80	643	
LT275/70R18 E	125/122Q	BSW	7.0- (8.0) -8.5	16.5	33.3	10.9	3640	3305	80	624	
LT275/65R20 E	126/123Q	BSW	7.5- (8.0) -9.5	16.5	34.3	10.5	3750	3415	80	605	

OBSERVE® G3-ICE

SPECIFICATIONS

TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	APPROVED RIM WIDTH RANGE (IN.)	TREAD DEPTH (1/32")	INFLATED DIMENSIONS			MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
						OVERALL DIA. (IN.)	OVERALL WIDTH (IN.)	MAX LOAD (LBS)			
195/60R15	88T	SL	BSW	5.5- (6.0) -7.0	11.3	24.2	7.9	1235	44	858	
195/65R15	91T	SL	BSW	5.5- (6.0) -7.0	11.3	25.0	7.9	1356	44	831	
205/65R15	94T	SL	BSW	5.5- (6.0) -7.5	11.3	25.5	8.2	1477	44	816	
205/55R16	91T	SL	BSW	5.5- (6.5) -7.5	11.3	24.9	8.4	1356	44	835	
205/60R16	92T	SL	BSW	5.5- (6.0) -7.5	11.3	25.7	8.2	1389	44	809	
215/60R16	95T	SL	BSW	6.0- (6.5) -7.5	11.3	26.1	8.7	1521	44	795	
225/70R16	107T	XL	BSW	6.0- (6.5) -7.5	12.5	28.4	9.0	2149	50	731	
245/70R16	111T	XL	BSW	6.5- (7.0) -8.0	13.1	29.5	9.8	2403	50	704	
LT245/75R16	120/116Q	E	BSW	6.0- (7.0) -8.0	15.0	30.5	9.8	3042	80	682	
265/70R16	112T	SL	BSW	7.0-(8.0)-9.0	13.7	30.6	10.7	2469	44	678	
235/65R17	108T	XL	BSW	6.5- (7.0) -8.5	13.1	29.1	9.4	2205	50	715	

Speed rated "Q" = 99mph, "H" = 130mph, "T" = 118mph. "SL" = Standard Load, "XL" = Extra Load, "E" = 10-ply rating. "BSW" = Black Sidewall. Bold designates measuring rim width. For the latest tire information, please visit toyotires.com.

▲ WARNING

TIRES MUST NEVER BE OPERATED IN EXCESS OF THEIR RATED SPEED LIMIT.

Exceeding the tire's speed capability will cause overheating of the tire and sudden failure, possibly leading to loss of vehicle control. Toyo Tires passenger and light truck tires have a maximum speed rating depending on size and type. Consult your tire dealer or contact Toyo Tires at 800.442.8696 if you are not sure about the maximum speed rating of your tires. Toyo Tire U.S.A. Corp. does not endorse the operation of any vehicle in an unsafe or unlawful manner. Tire speed ratings do not imply that a vehicle can be safely driven at the speed for which the tire is rated. Speed ratings are based on laboratory tests, which relate to performance on the road, but are not applicable if tires are underinflated, overloaded, worn out, damaged, or altered.

EXERCISE DUE CARE WHEN OPERATING VEHICLES WITH MODIFIED SUSPENSIONS AND INCREASED GROUND CLEARANCE!

The installation of off-road type tires, combined with modified suspensions and increased ground clearance, can significantly alter the handling characteristics of a vehicle, including increased braking distances and changes to vehicle maneuverability and cornering capability. Such modified vehicles will perform differently from stock models. If you make sharp turns or abrupt maneuvers, the vehicle may roll over or go out of control and crash. Always wear seat belts and drive safely, recognizing that reduced speeds and specialized driving techniques may be required. You should read the driving guidelines and instructions in the owner's manuals provided by the manufacturers of both the vehicle and the suspension kit.

ALWAYS OBEY ALL VEHICLE AND TRAFFIC LAWS!

You are responsible for the legality and safety of any modifications to your vehicle, and for operating your vehicle in a safe and lawful manner. Consult your vehicle owner's manual, your local laws, and the vehicle suspension kit manufacturer before undertaking modifications to your vehicle suspension.

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials specifications, or availability without notice or obligation.

